



Aalborg Universitet

AALBORG UNIVERSITY
DENMARK

Flow field design for high-pressure PEM electrolysis cells

Olesen, Anders Christian; Kær, Søren Knudsen

Publication date:
2017

Document Version
Accepted author manuscript, peer reviewed version

[Link to publication from Aalborg University](#)

Citation for published version (APA):

Olesen, A. C., & Kær, S. K. (2017). *Flow field design for high-pressure PEM electrolysis cells*. Abstract from 1st International Conference on Electrolysis, Copenhagen, Denmark.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.

Abstract No (don't use) – Preference: oral

Flow field design for high-pressure PEM electrolysis cells

Anders Christian Olesen and Søren Knudsen Kær

Department of Energy Technology, Aalborg University, Pontoppidanstræde 111, 9220 Aalborg East
aco@et.aau.dk

Summary. To study the electrochemical behaviour of full-scale, flow field designs of high-pressure PEM electrolysis cells, a computational fluid dynamics model has been developed. For a set of specific operating conditions, different flow fields are investigated in terms of their ability to handle gas and heat management.

Abstract. With the increasing interest in producing hydrogen through water electrolysis, the importance of understanding the transport phenomena governing its operation increases. To ensure optimal operating conditions for PEM electrolysis, it is particularly important to understand how the liquid feed-water distributes. Water not only serves as a reactant, it also aids in cooling due to its high specific heat capacity. The movement of liquid water at the anode is difficult to model, since it is highly coupled to the formation of gas bubbles. To capture the complex two-phase flow behaviour that takes place within micro-channels and porous media, our research group has developed an Euler-Euler model in the computational fluid dynamics modelling framework of ANSYS CFX. In addition to two-phase flow, the model accounts for turbulence, species transport in the gas phase, heat transport in all three phases (i.e. solid, gas and liquid), as well as charge transport of electrons and ions. Our recent improvements have focused on the models ability to account for phase change and electrochemistry as well as the modelling of two-phase flow regimes.

For comparison, an interdigitated and parallel channel flow field will be investigated with regard to how well they distribute gas and heat. To obtain a high durability when operating at high current densities, it is essential that liquid water and temperature is evenly distributed over the entire active surface area. In Figure 1, a contour plot of the temperature distribution within an interdigitated flow field is presented as an example. The axis-symmetric simulation shows that the formation of hot spots in the order of 8°C above the inlet temperature can occur for a current density of 3 A/cm² and a water stoichiometry of 350. These spots are primarily located underneath the outlet channels. To avoid them, an in-depth design and simulation study is necessary.




Figure 1: Contour plot of the temperature distribution for an interdigitated flow field at a current density of 3 A/cm² and a water stoichiometry of 350.